



Propulsion Marine Engine Performance Data

Curve No. M-6007
DS : 4983
CPL : 5482
DATE: 4-Jul-19

General Engine Data

Engine Model	K38-M
Rating Type	Heavy Duty
Rated Engine Power	970 [1300]
Rated Engine Speed	1800
Rated Power Production Tolerance	3
Rated Engine Torque	5143 [3793]
Peak Engine Torque @ 1500 rpm.....	5330 [3931]
Brake Mean Effective Pressure	1715 [249]
Indicated Mean Effective Pressure.....	[N.A.]
Maximum Allowable Engine Speed	2375

Maximum Continuous Torque Capacity from Front of Crank Specifications

Maximum Torque Capacity from Front of Crank ²	4341 [3202]
Compression Ratio	15:1
Piston Speed	9.5 [1875]
Firing Order	1R-6L-5R-2L-3R-4L-6R-1L- 2R-5L-4R-3L
Weight (Dry) - Engine Only - Average	4218 [9300]
Weight (Dry) - Engine With Heat Exchanger System - Average.....	4538 [10005]
Weight Tolerance (Dry) Engine Only	3.8

Governor Settings

Default Droop Value.....	Refer to MAB 2.04.00-03/23/2006 for Droop explanation	6%
Maximum Droop Allowed.....		16%
High Speed Governor Break Point.....		1860
Minimum Idle Speed Setting		600
Normal Idle Speed Variation		25
High Idle Speed Range Minimum		1860
Maximum		1972

Noise and Vibration

Average Noise Level - Top	(Idle).....	89
	(Rated).....	104
Average Noise Level - Right Side	(Idle).....	89
	(Rated).....	102
Average Noise Level - Left Side	(Idle).....	89
	(Rated).....	103
Average Noise Level - Front	(Idle).....	85
	(Rated).....	104

Fuel System¹

Avg. Fuel Consumption - ISO 8178 E3 Standard Test Cycle	171.2 [45.2]
Fuel Consumption at Rated Speed	234.7 [62.0]
Approximate Fuel Flow to Pump	469.4 [124.0]
Maximum Allowable Fuel Supply to Pump Temperature	60.0 [140]
Approximate Fuel Flow Return to Tank	168.5 [44.5]
Approximate Fuel Return to Tank Temperature	71.2 [160]
Maximum Heat Rejection to Drain Fuel	2.8 [160]
Fuel Pressure - Pump Out/Rail .. Mechanical Gauge	724 [105]
INSITE Reading	N.A.

TBD= To Be Determined

N/A = Not Applicable

N.A. = Not Available

¹ Unless otherwise specified, all data is at rated power conditions and can vary \pm 5%.

² No rear loads can be applied when the FPTO is fully loaded. Max PTO torque is contingent on torsional analysis results for the specific drive system. Consult Installation Direction Booklet for Limitations.

³ Heat rejection to coolant values are based on 50% water/50% ethylene glycol mix and do NOT include fouling factors. If sourcing your own cooler, a service fouling factor should be applied according to the cooler manufacturer's recommendation.

⁴ Consult option notes for flow specifications of optional Cummins seawater pumps, if applicable.

⁵ May not be at rated load and speed. Maximum heat rejection may occur at other than rated conditions.

CHONGQING CUMMINS ENGINE CO.,Ltd.

CHONGQING, P.R.CHINA, 400031

All Data is Subject to Change Without Notice - Consult the following Cummins intranet site for most recent data:

<http://marine.cummins.com/>

Propulsion Marine Engine Performance Data

Curve No. **M-6007**
DS : **4983**
CPL : **5482**
DATE: **4-Jul-19**

Air System¹

Intake Manifold Pressure	kPa [in Hg]	200 [59]
Intake Air Flow	l/sec [cfm]	1298 [2750]
Heat Rejection to Ambient	kW [Btu/min]	78 [4440]

Exhaust System¹

Exhaust Gas Flow	l/sec [cfm]	3233 [6,850]
Exhaust Gas Temperature (Turbine Out)	°C [°F]	455 [850]
Exhaust Gas Temperature (Manifold)	°C [°F]	583 [1,080]

Emissions (in accordance with ISO 8178 Cycle E3)

NOx (Oxides of Nitrogen)	g/kw·hr [g/hp·hr]	6.49 [4.84]
HC (Hydrocarbons)	g/kw·hr [g/hp·hr]	0.13 [0.10]
CO (Carbon Monoxide)	g/kw·hr [g/hp·hr]	1.40 [1.04]
PM (Particulate Matter)	g/kw·hr [g/hp·hr]	0.13 [0.10]

Emissions (in accordance with ISO 8178 Cycle E2)

NOx (Oxides of Nitrogen)	g/kw·hr [g/hp·hr]	N.A.
HC (Hydrocarbons)	g/kw·hr [g/hp·hr]	N.A.
CO (Carbon Monoxide)	g/kw·hr [g/hp·hr]	N.A.

Cooling System¹

Sea Water Pump Specifications	MAB 0.08.17-07/16/2001	
Pressure Cap Rating (With Heat Exchanger Option)	kPa [psi]	103 [15]
Max. Pressure Drop Across Any External Cooling System Circuit	kPa [psi]	34 [5]

Engines with Low Temperature Aftercooling (LTA)

Main Engine Circuit

Coolant Flow to Main Cooler (with blocked open thermostat)	l/min [gal/min]	1117 [295]
Standard Thermostat Operating Range	Start to open.....°C [°F]	82 [180]
	Full open.....°C [°F]	95 [202]
Heat Rejection to Engine Coolant ³	kW [Btu/min]	365 [20800]

Aftercooler (LTA) Circuit

Coolant Flow to LTA Cooler (with blocked open thermostat)	l/min [gal/min]	288 [76]
LTA Thermostat Operating Range	Start to open.....°C [°F]	66 [150]
	Full open.....°C [°F]	80 [175]
Heat Rejection to Engine Coolant ³	kW [Btu/min]	140 [7970]
Maximum Coolant Inlet Temperature from LTA Cooler	°C [°F]	63 [145]

TBD= To Be Determined

N/A = Not Applicable

N.A. = Not Available

¹ Unless otherwise specified, all data is at rated power conditions and can vary ± 5%.

² No rear loads can be applied when the FPTO is fully loaded. Max PTO torque is contingent on torsional analysis results for the specific drive system. Consult Installation Direction Booklet for Limitations.

³ Heat rejection to coolant values are based on 50% water/50% ethylene glycol mix and do NOT include fouling factors. If sourcing your own cooler, a service fouling factor should be applied according to the cooler manufacturer's recommendation.

⁴ Consult option notes for flow specifications of optional Cummins seawater pumps, if applicable.

⁵ May not be at rated load and speed. Maximum heat rejection may occur at other than rated conditions.

CHONGQING CUMMINS ENGINE CO.,Ltd.

CHONGQING, P.R.CHINA, 400031

All Data is Subject to Change Without Notice - Consult the following Cummins intranet site for most recent data:

<http://marine.cummins.com/>