



CUMMINS INC.
Columbus, IN 47201
Marine Performance Curves

Basic Engine Model
KTA50-M2

Engine Configuration
D283033MX02

Curve Number:
M-6209


CPL Code:
8063

Date:
21-Sep-09

Displacement: **50 liter** [3068 in³]
Bore: **159 mm** [6.25 in]
Stroke: **159 mm** [6.25 in]
Fuel System: **PT (CENTRY AND V.S.)**
Cylinders: **16**
Rated Power: **1193 kw** [1600 bhp]
Rated Speed: **1800 rpm**
Rating Type: **Continuous Duty**
Aspiration: **Turbocharged / Low Temperature Aftercooled**

CERTIFIED: This diesel engine complies with or is certified to the following agencies requirements:

IMO - NOx requirements of the International Maritime Organization (IMO), MARPOL 73/78 Annex VI, Regulation 13



Speed	Full Throttle- Power		Full Throttle- Torque		Fuel Cons.- Prop. Curve 3.0 Exp.	
rpm	kw	(hp)	N·m	(ft·lb)	L/hr	(gal/hr)
1860	1193	(1600)	6125	(4517)		
1800	1193	(1600)	6329	(4668)	290.7	(76.8)
1700	1145	(1535)	6429	(4742)	240.1	(63.4)
1600	1093	(1466)	6522	(4811)	202.2	(53.4)
1500	1035	(1388)	6588	(4859)	168.6	(44.5)
1400	919	(1232)	6264	(4620)	138.3	(36.5)
1300	838	(1124)	6155	(4540)	111.6	(29.5)
1200	722	(967)	5741	(4234)	90.2	(23.8)

* Cummins Full Throttle Requirements:

- Engine achieves or exceeds rated rpm at full throttle under any steady operating condition
- Engines in variable displacement boats (such as pushboats, tugboats, net dragners, etc.) achieve no less than 100 rpm below rated speed at full throttle during a dead push or bollard pull
- Engine achieves or exceeds rated rpm when accelerating from idle to full throttle

Rated Conditions: Ratings are based upon ISO 15550 reference conditions; air pressure of 100 kPa [29.612 in Hg], air temperature 25deg. C [77 deg. F] and 30% relative humidity. Power is in accordance with IMCI procedure. Member NMMA. Unless otherwise specified, tolerance on all values is +/-5%.

Full Throttle curve represents power at the crankshaft for mature gross engine performance corrected in accordance with ISO 15550. Propeller Curve represents approximate power demand from a typical propeller. Propeller Shaft Power is approximately 3% less than rated crankshaft power after typical reverse/reduction gear losses and may vary depending on the type of gear or propulsion system used.

Fuel Consumption is based on fuel of 35 deg. API gravity at 16 deg C [60 deg. F] having LHV of 42,780 kJ/kg [18390 Btu/lb] and weighing 838.9 g/liter [7.001 lb/U.S. gal].

Continuous Rating (CON): Intended for continuous use in applications requiring uninterrupted service at full power. This rating is an ISO 15550 standard power rating.

CHIEF ENGINEER

Propulsion Marine Engine Performance Data

Curve No. M-6209
DS : 4998
CPL : 8063
DATE: 21-Sep-09

General Engine Data

Engine Model	KTA50-M2
Rating Type	Continuous Duty
Rated Engine Power	1193 [1600]
Rated Engine Speed	1800
Rated Power Production Tolerance	3
Rated Engine Torque	6329 [4668]
Peak Engine Torque @ 1500 rpm.....	6588 [4859]
Brake Mean Effective Pressure	1582 [229]
Indicated Mean Effective Pressure.....	3168 [459]
Maximum Allowable Engine Speed	2375
Maximum Torque Capacity from Front of Crank ²	4341 [3202]
Compression Ratio	13.9:1
Piston Speed	9.5 [1875]
Firing Order	1R-1L-3R-3L-2R-2L-5R-4L- 8R-8L-6R-6L-7R-7L-4R-5L
Weight (Dry) - Engine Only - Average	5166 [11389]
Weight (Dry) - Engine With Heat Exchanger System - Average.....	5742 [12659]
Weight Tolerance (Dry) Engine Only	10.0

Governor Settings

Default Droop Value.....	Refer to MAB 2.04.00-03/23/2006 for Droop explanation	6%
Minimum Droop Allowed.....		N/A
Maximum Droop Allowed.....		N/A
High Speed Governor Break Point.....		1860
Minimum Idle Speed Setting		650
Normal Idle Speed Variation		25
High Idle Speed Range Minimum		1860
High Idle Speed Range Maximum		2016

Noise and Vibration

Average Noise Level - Top	(Idle)..	dBa @ 1m	85
	(Rated)	dBa @ 1m	94
Average Noise Level - Right Side	(Idle)..	dBa @ 1m	84
	(Rated)	dBa @ 1m	93
Average Noise Level - Left Side	(Idle)..	dBa @ 1m	84
	(Rated)	dBa @ 1m	92
Average Noise Level - Front	(Idle)..	dBa @ 1m	84
	(Rated)	dBa @ 1m	92

Fuel System¹

Avg. Fuel Consumption - ISO 8178 E3 Standard Test Cycle	209.1 [55.2]
Fuel Consumption at Rated Speed	290.7 [76.8]
Approximate Fuel Flow to Pump	533.7 [141.0]
Maximum Allowable Fuel Supply to Pump Temperature	60.0 [140]
Approximate Fuel Flow Return to Tank	243.0 [64.2]
Approximate Fuel Return to Tank Temperature	65.4 [150]
Maximum Heat Rejection to Drain Fuel	3.2 [180]
Fuel Pressure - Pump Out/Rail . Mechanical Gauge	907 [132]
INSITE Reading	934 [136]

TBD= To Be Determined

N/A = Not Applicable

N.A. = Not Available

¹ Unless otherwise specified, all data is at rated power conditions and can vary $\pm$ 5%.

² No rear loads can be applied when the FPTO is fully loaded. Max PTO torque is contingent on torsional analysis results for the specific drive system. Consult Installation Direction Booklet for Limitations.

³ Heat rejection to coolant values are based on 50% water/50% ethylene glycol mix and do NOT include fouling factors. If sourcing your own cooler, a service fouling factor should be applied according to the cooler manufacturer's recommendation.

⁴ Consult option notes for flow specifications of optional Cummins seawater pumps, if applicable.

⁵ May not be at rated load and speed. Maximum heat rejection may occur at other than rated conditions.

CUMMINS ENGINE COMPANY, INC

COLUMBUS, INDIANA

All Data is Subject to Change Without Notice - Consult the following Cummins intranet site for most recent data:

<http://marine.cummins.com/>

Propulsion Marine Engine Performance Data

Curve No. M-6209
DS : 4998
CPL : 8063
DATE: 21-Sep-09

Air System¹

Intake Manifold Pressure	kPa [in Hg]	202 [60]
Intake Air Flow	l/sec [cfm]	1765 [3740]
Heat Rejection to Ambient	kW [Btu/min]	78 [4464]

Exhaust System¹

Exhaust Gas Flow	l/sec [cfm]	4115 [8720]
Exhaust Gas Temperature (Turbine Out)	°C [°F]	430 [806]
Exhaust Gas Temperature (Manifold)	°C [°F]	592 [1097]

Emissions (in accordance with ISO 8178 Cycle E3)

NOx (Oxides of Nitrogen)	g/kw-hr [g/hp-hr]	6.63 [4.94]
HC (Hydrocarbons)	g/kw-hr [g/hp-hr]	0.19 [0.14]
CO (Carbon Monoxide)	g/kw-hr [g/hp-hr]	0.59 [0.44]
PM (Particulate Matter)	g/kw-hr [g/hp-hr]	N.A.

Cooling System¹

Sea Water Pump Specifications	MAB 0.08.17-07/16/2001	
Pressure Cap Rating (With Heat Exchanger Option)	kPa [psi]	103 [15]
Max. Pressure Drop Across Any External Cooling System Circuit	kPa [psi]	34 [5]

Engines without Low Temperature Aftercooling (LTA)

Jacket Water Aftercooled Engine (JWAC)

Coolant Flow to Engine Heat Exchanger	l/min [gal/min]	1404 [371]
Standard Thermostat Operating Range (Start to Open)	°C [°F]	82 [180]
Standard Thermostat Operating Range (Full Open)	°C [°F]	95 [202]
Heat Rejection to Engine Coolant ³	kW [Btu/min]	690 [39300]

Engines with Low Temperature Aftercooling (LTA)

Two Loop LTA

Main Engine Circuit

Coolant Flow to Main Cooler (with blocked open thermostat).....	l/min [gal/min]	1117 [295]
Standard Thermostat Operating Range	Start to open.....°C [°F]	82 [180]
	Full open.....°C [°F]	95 [202]
Heat Rejection to Engine Coolant ³	kW [Btu/min]	479 [27264]

Aftercooler (LTA) Circuit

Coolant Flow to LTA Cooler (with blocked open thermostat).....	l/min [gal/min]	288 [76]
LTA Thermostat Operating Range	Start to open.....°C [°F]	66 [150]
	Full open.....°C [°F]	80 [175]
Heat Rejection to Engine Coolant ³	kW [Btu/min]	211 [12036]
Maximum Coolant Inlet Temperature from LTA Cooler.....	°C [°F]	71 [160]

TBD= To Be Determined

N/A = Not Applicable

N.A. = Not Available

¹ Unless otherwise specified, all data is at rated power conditions and can vary ± 5%.

² No rear loads can be applied when the FPTO is fully loaded. Max PTO torque is contingent on torsional analysis results for the specific drive system. Consult Installation Direction Booklet for Limitations.

³ Heat rejection to coolant values are based on 50% water/50% ethylene glycol mix and do NOT include fouling factors. If sourcing your own cooler, a service fouling factor should be applied according to the cooler manufacturer's recommendation.

⁴ Consult option notes for flow specifications of optional Cummins seawater pumps, if applicable.

⁵ May not be at rated load and speed. Maximum heat rejection may occur at other than rated conditions.

CUMMINS ENGINE COMPANY, INC

COLUMBUS, INDIANA

All Data is Subject to Change Without Notice - Consult the following Cummins intranet site for most recent data:

<http://marine.cummins.com/>